



# PORTABLE VISCOMETER

---

**VM-250.2**

**IN PROCESS TO EXCELLENCE**

# Specifications

## Measuring range:

Dynamic Viscosity	Up to 10000 mPa·s (cP)
Viscosity calibration	0,1-100 mPa·s (cP) 1-1000 mPa·s (cP) 10-10000 mPa·s (cP)
Temperature	-40... +85°C (-40... +185°F)

## Accuracy:

Dynamic Viscosity	±1% of span
Temperature	±0.1°C (±0.2°F) or ±0.2°C (±0.4°F)

## Repeatability:

Dynamic Viscosity	±0,5% of span
Temperature	±0.1°C (±0.2°F)

Ambient temperature -40... +85°C (-40... +185°F)

Depth of submersion Up to 30 meters (100 ft.)

## Sensor:

Type	Vibrating element (Resonance principle)
Material	Stainless steel SS 316 L; NiSpan C; Hastelloy C22

## Intrinsically safe:

Controller	ATEX II (2G) EEx ib [ia] IIB T4
Sensor	ATEX II 1G EEx ia IIB T4

Power supply NiMH 3.6V-1500 mAh

Operating time without charging Appr. 12 hours

## Dimensions:

Level block with viscosity meter	420 x 245 x 140 mm (16.5 x 9.6 x 5.5"), 4 kg (8.8 lb)
Sensor	220 x ø42 mm (8.7 x ø1.7"), 1 kg (2.2 lb)
Controller	180 x 80 x 40 mm (7.1 x 3.2 x 1.6"), 0.6 kg (1.3 lb)

Temperature compensation Automatic

Viscosity compensation Automatic

Reporting formats Dynamic viscosity in mPa·s or cP; temperature in °C or °F

Backlighted LCD display (2x16)

Local memory up to 2000

Build in Bluetooth for data transfer to printer or PC

Optional Windows - based software

Data handling

## Advantages

- Direct viscosity measurement
- Record level viscosity and average per tank
- Automatic temperature compensation operation
- No sampling required
- ATEX Hazloc certification, IEC
- Record level of liquid
- At any depths up to 30 meters
- Local results storage and Bluetooth data
- Safe operation, low maintenance
- Rigid construction for heavy duty outdoor

## Applications


- Viscosity and Temperature profile in storage tank
- Product consistency and adulteration check
- Viscosity control at outlets and delivery points
- In-tank blending and mixing control
- Food, milk and dairy products
- Petroleum products ,fuels, lubricants

Delivered in compact carrying case



CASE

Able to download the measurements to PC;  
Multifunctional software allows to proceed the  
measurements results in user-convenient form;  
Compatible for a Windows XP/Vista/7.



SOFTWARE

Immediate printout of the measurements;  
No need for PC.



BLUETOOTH PRINTER

**For more information please visit [www.lemis-process.com](http://www.lemis-process.com)**



**USA**  
**LEMIS USA, Inc.**  
2121 Golden Road, Suite 2A  
The Woodlands  
TX 77380, USA  
Ph.: +1 281 465 8441  
Fax: +1 281 465 8224

**EUROPE**  
**AS LEMIS Baltic**  
26 Ganību dambis  
Rīga, LV-1005  
Latvia, EU  
Ph.: +371 6738 3223  
Fax: +371 6738 3270

**INDIA**  
**LEMIS India PVT LTD**  
603, Platinum Technopark, Plot-17/18  
Sector-30A, Vashi  
Vashi - Navi Mumbai. 400705, INDIA  
Ph.: +91 22 6721 5655  
Fax: +91 22 6794 2666

**E-mail: [info@lemis-process.com](mailto:info@lemis-process.com)**